

INDROMATIC

Upgraded Packaged Reverse Osmosis Systems

Scarcity of clean water has increased our dependence on ground water sources. However, this water is unfit for drinking or for industrial use unless properly treated. Reverse osmosis, a membrane desalination process increasingly used worldwide, purifies brackish water for drinking and industrial purposes.

Reverse osmosis membrane technology produces water with very low dissolved solids and which is also free from particulate, colloidal and organic matter.

Features

- Housed in a well designed cabin modelled mild steel epoxy painted skid
- FRP moulded control & wet panels for longer life with added protection
- Operation control by microprocessor
- Auto or manual control of entire RO system
- GSM based one way remote monitoring system
- MIMIC for the complete RO operation
- Built in safety features to protect high pressure pump & membranes
- Additional protection (Dry run / Overload / Single Phase) for high pressure pump
- Provision for auto dosing
- Metering and control of RO system, based on product water quality
- Online sensor to measure permeate flow rate and total value
- Efficiently removes up to 95% of total dissolved solids (TDS) or salinity to produce water that is clear and pleasant to taste
- Range of models with capacities from 400 - 1000 litres/h
- Capable of handling waters with TDS levels up to 2500 ppm (based on model)
- Fault condition notification by means of SMS alerts
- High level treated water tank indication to prevent overflow



Optional Features

- Microprocessor based auto flushing

Advantages

- The most economical & efficient method of dissolved solids removal
- Easy to start up and user friendly operation. Lesser footprints
- Can handle fluctuations of total dissolved solids (TDS) in feed water
- Easy availability of spares and service
- Short delivery periods

Applications

- Providing safe drinking water for hotels, restaurants, hospitals and residences
- Mineral water plants
- Laboratory water
- Pre-treatment to deionisation system, in turn reduces chemical consumption and operating cost
- In pharmaceutical processes
- In providing water with reduced scaling potential to boilers

Technical Data

Model	INDROMATIC 402	INDROMATIC 403	INDROMATIC 404	INDROMATIC 405
Average Product Flow (LPH)	400	600	800	1000
*Average Recovery (%)	30	30	30	30
*Maximum Permissible TDS in feed (ppm)	2500	2500	2500	2500
Average TDS Removal (%)	Between 90 to 95			
Minimum Feed Pressure required at Pump inlet (kg/cm ²)	Not less than 2 .0			
Power Supply	415V/50HZ			
Motor HP /RPM	3.0/2900			
Dimensions (Width x Depth x Height x Head Room)	850 mm x 650 mm x 1630 mm x 1000 mm			

Note: *Higher recovery & TDS levels are possible. Contact us with detailed raw water analysis for confirmation.
Feed water temperature should not be above 40 degrees centigrade.

To the best of our knowledge the information contained in this publication is accurate. Ion Exchange (India) Ltd. maintains a policy of continuous development and reserves the right to amend the information given herein without notice.

INDION® is the registered trademark of Ion Exchange (India) Ltd.

ION EXCHANGE INDIA LTD.

Corporate Office

Ion House, Dr. E. Moses Road,
Mahalaxmi, Mumbai 400 011
Tel: +91 22 3989 0909
Fax: +91 22 2493 8737
E-mail: ieil@ionexchange.co.in

International Division

R-14, T.T.C MIDC, Thane - Belapur Road,
Rabale, Navi Mumbai 400 701
Tel: +91 22 3989 0909 / 3047 2400
Fax: +91 22 2769 7918
E-mail: rabcrointl@ionexchange.co.in
export.sales@ionexchange.co.in

Chemical Division

4th Flr, Riviera Apartment, Dwarkapuri Colony,
Punjagutta, Hyderabad 500 082
Tel: +91 40 3066 3101 / 02 / 03
Fax: +91 40 3066 3104
E-mail: hydcro@ionexchange.co.in

OFFICES

Regional	Telephone	Fax	E-mail
Chennai	+91 44 3989 0909 / 3910 2900	+91 44 2815 3361	checro@ionexchange.co.in
Delhi	+91 11 3989 0909 / 3054 3200	+91 11 2577 4837	delcro@ionexchange.co.in
Kolkata	+91 33 3989 0909 / 3043 3400	+91 33 2400 4345	calcro@ionexchange.co.in
Vashi	+91 22 3989 0909 / 3913 2300	+91 22 2788 9839	mumcro@ionexchange.co.in
Branch			
Bengaluru	+91 80 2204 2888		bngcro@ionexchange.co.in
Bhubaneswar	+91 674 326 9525 / 257 1491		bbsr@ionexchange.co.in
Chandigarh	+91 172 274 5011	+91 172 274 4594	delcro@ionexchange.co.in
Hyderabad	+91 40 3066 3101 / 02 / 03	+91 40 3066 3104	hydcro@ionexchange.co.in
Lucknow	+91 522 319 9911	+91 11 2577 4837	lko.general@ionexchange.co.in
Vadodara	+91 265 302 7489 / 90	+91 265 239 8508	brdcro@ionexchange.co.in
Visakhapatnam	+91 891 324 6253		sales.vizag@ionexchange.co.in

Factories: Ankleshwar | Hosur | Patancheru | Rabale | Verna

All India Service and Dealer Network

www.ionindia.com